

Spécifications taillants fond de trou

ø taillant (mm)	poids	pour marteau	ø extérieur marteaux (mm)
2 5/8" (66)	2	2"	58
3" (76)	3		
3 5/8" (92)	5	3" 1/2	85
3 3/4" (95)	5		
3 7/8" (100)	5		
4" (102)	5		
4 1/8" (105)	6		
4 1/8" (105)	8		
4 1/4" (108)	8		
4 1/2" (115)	8		
4 3/4" (121)	8		
5" (127)	9		
5 1/8" (130)	9		
6" (152)	10		
5 1/2" (140)	17	5"	116
5 3/4" (146)	18		
6" (152)	19		
6 1/8" (156)	19		
6 1/2" (165)	20		
8" (203)	23		
6" (152)	25		
6 1/8" (156)	25		
6 1/4" (159)	26		
6 1/2" (165)	26		
6 3/4" (172)	26		
7" (178)	27		
7 1/2" (191)	28		
8" (203)	30		
9 1/4" (235)	42		
10" (254)	48		
12 1/4" (311)	98		
7 5/8" (194)	50	8"	180
8 1/2" (216)	56		
10" (254)	65		
10" (254)	105	10"	225
12" (305)	120		
11 7/8" (302)	145	12"	274
15" (381)	230		
15" (381)	300	12"	320
17 1/2" (445)	340		
17 1/2" (445)	360	15"	357
20" (508)	500		
20" (508)	565		
22" (559)	620	15", 18", 20"	
24" (610)	730		
24" (610)	985		
26" (660)	1,060	24"	520
33" (838)	1,500		
38 3/8" (975)	2,350	TD700	650
33" (838)	2,275	33"	758
36" (914)	2,410		
40" (1016)	3,420		
43" (1092)	3,550		

>> **Autres types et diamètres sur demande**

>> **Différents emmanchements sont disponibles**